

ProxiPen



Compact Reader for RFID Tags

In today's rapidly-changing information society, large corporations and small companies alike increasingly require modern data collection and auto-ID systems. To meet these demands, GCS has developed an innovative data acquisition unit, the "ProxiPen." The ProxiPen reads radio frequency identification (RFID) tags and other transponders automatically, and can fully satisfy the data collection needs of both commercial and industrial applications.



Benefits -

- ProxiPen can read RFID tags even if they are wet, frosty, dirty, greasy, or painted over
- RFID tags can be concealed behind wallpaper, wallboard, plaster, paneling, mirrors or any other nonmetallic surface - a real plus in applications where aesthetics or vandalism are considerations
- ProxiPen "autosenses" and reads RFID tags whenever they come into its reading range
- Low power consumption - requires one "AA" commercial alkaline, lithium or rechargeable battery that can be replaced by user without any special tools
- High memory capacity (4,063 readings) - can be used for long periods in the field without the need for frequent downloading
- Easy to use; no external controls

Features -

- Compact, lightweight, simple to operate
- Tough waterproof polycarbonate housing
- Resists heat, shock and hydrocarbons
- Powered by one "AA" commercial alkaline, lithium or rechargeable battery
- Reads RFID proximity tags
- Provides visible and audible indications to confirm information has been read

Applications -

- Guard Tour
- Maintenance
- Recording Service Activities
- Cleaning
- Attendance

Technical Information -

- Dimensions: 7.48"L x 1.26"W x 0.98"H (L190 x W32 x H25mm)
- Weight: 4.94 oz. (140g)
- Operating Temperature Range: -4°F to +158°F (-20°C to +70°C)
- Internal Protection Grade: ProxiPen: IP64; Sokymat TAGS: IP67
- Mechanical Shock Resistance: Free fall from 5 ft. (1.5m) on concrete
- TAG Frequency: 125 kHz
- Reading Distance: 0.12" to 0.71" (3-18mm) depending on size of transponder and condition of battery. Reads through nonmetallic materials.
- Approved Tags: Sokymat World TAG (Unique), dia. 1.18" (30mm); Sokymat World TAG (Nova), dia. 0.79"/1.18"/1.97" (20/30/50mm); Sokymat Tear Shape (Keyholder) and Wrist Band
- Memory Capacity: 4,063 readings
- Time Resolution: 1 minute
- Data Transfer: By RFID; 2,400 to 115,200 Baud
- Download Time: Approx. 1 minute (full memory)
- Housing: Polycarbonate
- Potting Material: Silicon or equivalent
- Power Supply: One "AA" cell, 1.5v
- Recommended Batteries: Duracell® Ultra, Energizer® e2 Photo Lithium, Sanyo® Twicell 1600 Ni-MH Rechargeable
- Time Permitted for Battery Change: 3 minutes maximum
- Battery Life in Standby Mode: Approx. 1 year
- Number of Readings with one Approved Alkaline Battery: Approx. 50,000
- EMC (Electromagnetic Compatibility): EN 55022, EN 61000 4-3, EN 61000 4-2
- Firmware: Flash-upgradeable
- Accessories: Leather holster with belt clip

Detex Limited Warranty

3-Year Limited Manufacturers Warranty



The E. C. Cush Company
9009 Wildberry Court
Boonsboro, MD 21713

Office: (301) 354-6064
Fax: (240) 597-2456

www.eccush.com

Detex Distributor Since 1948